

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/09/2013 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

 Product form
 : Substance

 Trade name
 : OTBCHA

 CAS No
 : 88-41-5

 Product code
 : O2000

 Formula
 : C12H22O2

Synonyms : 1-acetoxy-2-tert-butylcyclohexane / 2-(1,1-dimethylethyl)cyclohexanol acetate / 2-teriary-

butylcyclohexanol acetate / 2-tert-butylcyclohexanol acetate / 2-tert-butylcyclohexyl acetate / cyclohexanol, 2-(1,1-dimethylethyl)-, acetate / grumex / Substances with a flash-point above 60 °C and not more than 100 °C / Substances with a flash-point above 60 °C and not more than

100 °C, which do not belong to another class

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

CHEMTEX USA 27-29 Dwight Place Fairfield, 07004 - USA

T 862-702-8900 - F 862-702-8180

contact@chemtexusa.com - www.chemtexusa.com

### 1.4. Emergency telephone number

Emergency number : CHEMTEL:(800)255-3924

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification (GHS-US)

Flam. Liq. 4 H227 Skin Irrit. 2 H315 Eye Irrit. 2A H319 STOT SE 3 H336 STOT SE 3 H335 Asp. Tox. 1 H304 Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### 2.2. Label elements

### **GHS-US** labeling

Hazard pictograms (GHS-US)







GHS07 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

P261 - Avoid breathing dust, fume, gas, mist, spray, vapors

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear eye protection, face protection, protective clothing, protective gloves P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER

P302+P352 - If on skin: Wash with plenty of water

06/03/2015 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a doctor, a POISON CENTER if you feel unwell

P321 - Specific treatment (see supplemental first aid label on this label)

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use carbon dioxide (CO2), foam to extinguish

P391 - Collect spillage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Name	Product identifier	%	Classification (GHS-US)
OTBCHA (Main constituent)	(CAS No) 88-41-5	100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

4.11	Description	. 0	ıı ot u	ia ilicasare
First-aid	d measures ge	neral		

First-aid measures after ingestion

: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where

First-aid measures after inhalation : Remove the victim into fresh air. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Soap may be used. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get

medical advice/attention. Specific treatment (see ... on this label).

First-aid measures after eye contact

: Rinse cautiously with water for several minutes. Rinse immediately with plenty of water for 15 minutes. Take victim to an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Rinse mouth with water. Ingestion of large quantities: immediately to hospital. Call Poison

Information Centre (www.big.be/antigif.htm). Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the respiratory tract. Irritation of the

nasal mucous membranes. May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Tingling/irritation of the skin. Causes skin irritation.

Symptoms/injuries after eye contact : Irritation of the eye tissue. Causes serious eye irritation.

06/03/2015 EN (English US) 2/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Polyvalent foam. BC powder. Carbon dioxide. Foam. Dry powder. Carbon dioxide. Water spray.

Sand.

Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium. Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : DIRECT FIRE HAZARD. Material presenting a fire hazard. INDIRECT FIRE HAZARD.

Temperature above flashpoint: higher fire/explosion hazard. Combustible liquid.

Explosion hazard : DIRECT EXPLOSION HAZARD. No data available on direct explosion hazard. INDIRECT

EXPLOSION HAZARD. No data available on indirect explosion hazard. May form

flammable/explosive vapor-air mixture.

Reactivity : Upon combustion: CO and CO2 are formed.

#### 5.3. Advice for firefighters

Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and

windows.

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Avoid (reject) fire-fighting water to enter environment.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus. Do not enter fire area without proper

protective equipment, including respiratory protection.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective clothing

Emergency procedures : Mark the danger area. No naked flames. Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.

Methods for cleaning up

: Take up liquid spill into inert absorbent material, e.g.: sand/earth. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling

: Comply with the legal requirements. Keep away from naked flames/heat. At temperature > flashpoint: use spark-/explosionproof appliances. Finely divided: spark- and explosionproof appliances. Finely divided: spark- and explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe normal hygiene standards. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Use

only outdoors or in a well-ventilated area.

06/03/2015 EN (English US) 3/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Wash ... thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof

place. Keep container tightly closed.

Incompatible products : Strong bases. strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources. Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents. (strong) acids. (strong) bases.

Storage area : Store in a dry area. Ventilation at floor level. Keep only in the original container. Meet the legal

requirements.

Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. opaque. correctly labelled. meet the legal

requirements. Secure fragile packagings in solid containers.

Packaging materials : MATERIAL TO AVOID: plastics.

#### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

OTBCHA (88-41-5)	
ACGIH	Not applicable
OSHA	Not applicable

#### 8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Materials for protective clothing : GIVE EXCELLENT RESISTANCE: No data available. GIVE GOOD RESISTANCE: No data

available. GIVE LESS RESISTANCE: No data available. GIVE POOR RESISTANCE: No data

available.

Hand protection : Gloves. Wear protective gloves.

Eye protection : Safety glasses. Chemical goggles or safety glasses. Skin and body protection : Protective clothing. Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. Wear respiratory protection.

Other information : When using, do not eat, drink or smoke.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

Color : Colourless

Odor : No data available on odour

Odor threshold : No data available pH : No data available Melting point : No data available Freezing point : No data available Boiling point : 112 °C (24 hPa)

Flash point : 89 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : < 1 hPa

06/03/2015 EN (English US) 4/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : 0.94 Relative vapor density at 20 °C : 6.85

Molecular mass : 198.34 g/mol

Solubility : Insoluble in water. Soluble in ethanol.

Log Pow : No data available
Log Kow : No data available

Auto-ignition temperature : 285 °C

Decomposition temperature : No data available Viscosity : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available

9.2. Other information

Other properties : Gas/vapour heavier than air at 20°C. Slightly volatile.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Upon combustion: CO and CO2 are formed.

#### 10.2. Chemical stability

No data available. Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

strong acids. Strong bases.

## 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

OTBCHA (88-41-5)	
LD50 oral rat	4600 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
ATE US (oral)	4600.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the respiratory tract. Irritation of the

nasal mucous membranes. May cause respiratory irritation. May cause drowsiness or

dizziness.

Symptoms/injuries after skin contact : Tingling/irritation of the skin. Causes skin irritation.

06/03/2015 EN (English US) 5/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Irritation of the eye tissue. Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - water : Mild water pollutant (surface water). Ground water pollutant. No data available on ecotoxicity.

Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

OTBCHA (88-41-5)	
Persistence and degradability	Biodegradability in water: no data available. May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

OTBCHA (88-41-5)	
Bioaccumulative potential	No bioaccumulation data available. Not established.

### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations

: Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Use appropriate containment to avoid environmental contamination. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous

Additional information

Hazardous waste according to Directive 2008/98/EC. Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials

: Avoid release to the environment. Hazardous waste due to toxicity.

## **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s., 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

3

Packing group (DOT) : III - Minor Danger

Dangerous for the environment : Yes

06/03/2015 EN (English US) 6/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

**DOT Symbols** 

DOT Special Provisions (49 CFR 172.102)

: G - Identifies PSN requiring a technical name

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

### **Additional information**

Other information : No supplementary information available.

**ADR** 

: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, (E) Transport document description

Packing group (ADR) : 111

Class (ADR) : 9 - Miscellaneous dangerous substances and articles

Hazard identification number (Kemler No.) : 90 Classification code (ADR) : M7

Hazard labels (ADR) : 9 - Miscellaneous dangerous compounds



Orange plates

90

Tunnel restriction code (ADR) : E Limited quantities (ADR) : 5kg Excepted quantities (ADR) : E1

Transport by sea

UN-No. (IMDG) : 3077

06/03/2015 EN (English US) 7/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IMDG) : 9 - Miscellaneous dangerous compounds
Packing group (IMDG) : III - substances presenting low danger

MFAG-No : 171

Air transport

UN-No. (IATA) : 3077

Proper Shipping Name (IATA) : Environmentally hazardous substance, solid, n.o.s.

Class (IATA) : 9 - Miscellaneous Dangerous Goods

Packing group (IATA) : III - Minor Danger

Civil Aeronautics Law : Miscellaneous dangerous substances & articles

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

## OTBCHA (88-41-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

### **CANADA**

No additional information available

#### **EU-Regulations**

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R36/38

Full text of R-phrases: see section 16

### **National regulations**

No additional information available

### 15.3. US State regulations

No additional information available

## **SECTION 16: Other information**

Other information : None.

### Full text of H-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

06/03/2015 EN (English US) 8/9

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Disclaimer:

150 River Road, Suite G3B, Montville, NJ 07045. Ph. # (973) 335-2500; Fax # (973) 335-2552.

CHEMTEX USA, INC. Provides the information contained herein in a good faith but makes no representation as to its comprehensiveness or accuracy. Certain data contain in this document is taken from literature and or referred from other sources available in the web. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose and take the responsibility for observing existing laws and regulations.

06/03/2015 EN (English US) 9/9